

# Specifications

MODEL	B6022HSB-1 B6022HSB-2	B6622HSB-1 B6622HSB-2 B6622HSB-3	B7422HSB-1 B7422HSB-2	B7424HSB-3 B7424HSB-4	B8424HSB-3 B8424HSB-4	B84SB (PTO DRIVE)
Cutting width	60"	66"	74"	74"	84"	84"
Cutting height	28"	30"	30"	30"	30"	30"
Mount type	Skid steer	Skid steer	Skid steer	Skid steer	Skid steer	Cat. III, 3-point
Hydraulic requirements	13 - 22 GPM 2000 psi min.	13 - 22 GPM 2000 psi min.	13 - 22 GPM 2000 psi min.	20 - 32 GPM 2000 psi min.	20 - 32 GPM 2000 psi min.	10 GPM 1000 psi min.
System controls & drive	Hydraulic load sensing Block flow adjustable	Hydraulic load sensing Block flow adjustable	Hydraulic load sensing Block flow adjustable	Hydraulic load sensing Block flow adjustable	Hydraulic load sensing Block flow adjustable	PTO w/shear pin
Fan	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade
Fan diameter	21 ½"	21 ½"	21 ½"	23 ½"	23 ½"	23 ½"
Fan depth	7 ½"	7 ½"	7 ½"	7 ½"	7 ½"	7 ½"
Replaceable fan housing	7 gauge	7 gauge	7 gauge	7 gauge	7 gauge	7 gauge
Auger diameter	15"	15"	15"	15"	20"	20"
Auger center diameter	3" od x 0.250 wall	3" od x 0.250 wall	3" od x 0.250 wall	3" od x 0.250 wall	3" od x 0.250 wall	3" od x 0.250 wall
Auger thickness	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Drive fan	Hydraulic w/#80 chain	Hydraulic w/#80 chain	Hydraulic w/#80 chain	Hydraulic w/#80 chain	Hydraulic w/#80 chain	Hydraulic w/#80 chain
Drive auger	Hydraulic w/#60H chain	Hydraulic w/#60H chain	Hydraulic w/#60H chain	Hydraulic w/#60H chain	Hydraulic w/#60H chain	#60H chain
Body housing	10 gauge	7 gauge	7 gauge	7 gauge	7 gauge	7 gauge
Spout rotator	Hydraulic - 230°	Hydraulic - 230°	Hydraulic - 230°	Hydraulic - 230°	Hydraulic - 230°	Hydraulic - 230°
Spout deflector	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Cutting edge	½" x 4" beveled Replaceable	½" x 4" beveled Replaceable	½" x 4" beveled Replaceable	½" x 4" beveled Replaceable	½" x 4" beveled Replaceable	½" x 4" beveled Replaceable
Skid shoes	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable
Truck loading spout	Optional	Optional	Optional	Optional	Optional	Optional
Weight	1070 lbs	1260 lbs	1280 lbs	1193 lbs	1305 lbs	1317 lbs

