

FOOTNOTES

A - Z

A Q7357 will not fit D17 series 4 tractor
 B Side panel modification required
 C Must sign damage waver when ordering kit for 310 Belarus
 D If tractor equipped with Husco Hydraulic System (HHS) order X2175 hose kit "C". If no (HHS) order X2159 hose kit "C"
 E For tractors made in 1982 and earlier (3 cyl)
 F For tractors with hydrostatic transmissions
 G Fits tractors with a Woods L306 belly mount mower
 H For tractors made without chain drive.
 I For tractors made in 1985 and earlier
 J Front weight bracket must be removed.(to fit grill guard or loader interference)
 K Battery box must be modified
 L TSL/HSL loader does not fit this application
 M For models with centre drive shaft
 N For tractors with hydrostatic or standard transmissions
 O Will fit tractor with cab only
 P For tractors made in 1985 or later
 Q Will accept belly mount mower
 R For tractors made in 1987 and earlier
 S For tractors made in 1988 and later
 T Will accommodate Case IH M160 belly mower
 U For 1978 models and older
 V STD designated a non adjustable wheatland axle. These tractors have a wider chassis
 W Proto-type mtg. was fitted to standard transmission tractor
 X For older tractor with 4 blt. pattern on both sides, newer models are longer and have 8 blt. on rt. side, this mnt. won't fit
 Y Fits newer models with an 8 bolt pattern on right side
 Z For selectomatic model

BC Mtg. also fits general purpose models
 BD Fits USA model with a Hinson Cab
 BE Not for three cylinder tractors
 BF If tractor is equipped with "Grenco" cab, modification required to accommodate loader
 BG Proto-type mtg. kit was fitted to "rowcrop" model tractor
 BH Before placing order check with manufacturer for correct hole mounting pattern
 BI D series front wheels must be set 84" outside to outside
 BJ Side Exhaust
 BK Tractor with belly mower R60-IH use X9038 mower mnt. at added cost. (Mower model RC60B does not require X9038)
 BL Mtg. is for tractors with serial # starting at 60000 and over
 BM Fits tractors with a glide shift transmission
 BN Kubota RC-44-42 belly mower will fit with X9476 Mounting
 BO Will accommodate RC.54-71B model mower
 BP Front wheel spacing must be 52" C/C
 BQ C1568 consists of Q1434 mtg. kit and X9869 air valve
 BR Does not fit SU models
 BS Will fit with 42" Kubota midmount mower
 BT Mounted with aftermarket cab, not factory cab.
 BU Axle bars may have to be modified to fit some tractors
 BV Will not fit older model 310 with drive shaft off centre
 BW Rear mounting bracket bolts to sides of tractor
 BX Tractors before mid 1967 rear mtg bolts to underside
 BY For tractors made after mid 1967 - rear mounting bolts to sides of tractor
 BZ Rear mounting bracket bolts to underside of tractor

CA - CZ

CA For tractors with mounting holes underneath (belly mount)
 CB For tractors with mounting holes on the side
 CC Not for tractors with radius arms
 CD Remove existing side plates before installing mounting
 CE SN C45009 (4wd) & C49189 (2wd) and on denotes 'D' Series excluding 362.
 CF SN C45008 and earlier denotes 'C' series.
 CG May require O/C valve if gear/vane type pump present.
 CH Fuel tank must be R & R for mount kit installation.
 CI Tractor panel mount needs modification to accommodate mtg
 CJ No axle bars on mtg. kit, this will accomodate opt. fuel tank
 CK Mtg. does not have rear axle braces
 CL Extra holes must be drilled in rear axle braces
 CM Will not fit R.C. MODELS
 CN Do not exceed 2.5" lift cyl. (overload to tractor possible)
 CO Do not exceed 3.0" lift cyl. (overload to tractor possible)
 CP Q9520 mtg. front hole spacing is 11.68", Q9521 and Q9578 mtg. front hole spacing is 15.06"
 CQ For Prairie Cab only. Mtg. not suitable for tractors without
 CR For 4 cylinder engine only, for 3 cylinder use Q8562
 CS Does not fit low profile tractors
 CT C1234 consists of mtg. Q9938, axle brackets X8415, and fuel tank brackets X8422
 CU C1093 consists of mtg. Q9864 and air valve kit X9869
 CV Fits tractors with a maximum front tire size 14.9x24
 CW Fits tractors with a maximum front tire size 16.9x24
 CX Mtg. was fitted to tractor with 9.5x20 front tires
 CY Mtg. was fitted to tractor with 14.9xR24 front tires
 CZ Mtg. was fitted to tractor with 13.6xR24 front tires

AA - AZ

AA For tractor with cab only
 AB Loader must be removed to remove tractor side panels
 AC Mtg. does not fit with a belly mounted mower
 AD Will not fit with hydrostatic drive
 AE For tractors made in 1986 and later
 AF For tractors with Simms Cab
 AG For tractors made in 1965 & later (North American made)
 AH Mtg. is for tractors with Roll Over Protection Structure (ROPS)
 AI For tractors with serial # prefix "c" where front mounting bolts to front of tractor
 AJ For tractors made in 1990 and earlier
 AK For standard transmissions only
 AL For tractors with a British Ford cab
 AM Kit must be modified to allow Ford 914 belly mount mower
 AN For rowcrop tractor with a Hinson Cab
 AO Fits tractors with a 3 point hitch
 AP Mtg. was fitted to tractor with 14.9x26 front tires
 AQ Q9191 mtg. is for " Orchard " models only
 AR If fitted to 400A tractor there will be no dig
 AS For American built model tractor only
 AT For tractors with adj. front axle and four bolt front mount
 AU Mtg. holes will have to be increased in size to fit bolts
 AV Mtg. has three bolt front mount
 AW Mtg. has four bolt front mount
 AX Does not fit British built tractors
 AY For swept back axle use Q8029
 AZ Tractor must be equipped with John Deere side plates

BA - BZ

BA Will not fit flat deck tractor
 BB For contour chassis

DA - DZ

DA Mtg. was fitted to tractor with 16.9x30 front tires
 DB Mtg. was fitted to tractor with 14.9x30 front tires
 DC Larger tires than 14.9x28 will interfere with mounting kit
 DD Mtg. was fitted to tractor with 11.2x20 front tires
 DE Mtg. was fitted to tractor with 13.6x20 front tires

DF Remote valve section AL118486 required from John Deere.
 DG Mtg. was fitted to tractor with 7.50x16 front tires
 DH Mtg. was fitted to tractor with 6.0x16 front tires
 DI Modification required to axle bars for 30" rear wheel spacing
 DJ Mtg. was fitted to tractor with 20x8.00x10 front tires
 DK Mtg. was fitted to tractor with 27x10.50x15 NHS front tires
 DL Mtg. was fitted to tractor with 25x10.5x15 front tires
 DM Max front tire size of 13.9x24 will accommodate mounting
 DN Mtg. was fitted to tractor with 8.3x24 front tires
 DO Tractors with turf tires only
 DP Tire size 18.4x38 rear & 13.6x28 front (Firestone)
 DQ Tires - 14.9x26 fnt. are too large to accommodate mounting
 DR Tire size must be 8.3x24 front and 13.6x28 rear
 DS If tractor is equipped with front tires larger than 9.5 but no more than 11.2 use 595 loader, not S595
 DT Maximum front tire size to accommodate loader is 11.2x24
 DU Maximum front tire size to accommodate loader is 8.3x24
 DV Maximum front tire size to accommodate loader is 12.4x24
 DW Maximum front tire size to accommodate loader is 11.4x24
 DX Mtg. was fitted to hyd shuttle model with 20x8.00x10 front tires (turf) and 5x12 front tires (AG)
 DY Mtg. was fitted to tractor with 14.9x28 front tires
 DZ Mtg. was fitted to tractor with 16.9x28 front tires

EA - EZ

EA Mtg. was fitted to tractor with 25x8.50x14 (turf) tire
 EB Tractors with 16.9x28 front tires need to be spaced 82" C/C
 EC Mtg. to orchard model with 250/80-R16 front tires
 ED For front tire sizes larger than 14.9x24 use 695 loader
 EE Mtg. was fitted to tractor with 11.2x24 front tires
 EF Mtg. was fitted to tractor with 9.5Lx15 front tires
 EG Mtg. was fitted to tractor with 13.6x28 front tires
 EH Will not accommodate turf tires
 EI Mtg. was fitted to tractor with 8.5x34 front tires
 EJ Mtg. was fitted to tractor with 27x8.5x15 NHS front tires and Kioti belly mount mower
 EK Mtg. fitted to tractor with 212x180D15 (turf) front tires
 EL Mtg. was fitted to tractor with 8x16 front tires
 EM Mtg. was fitted to tractor with 6x12 front tires
 EN Mtg. was fitted to tractor with 4.5x10 front tires
 EO Remote valve section AL77030 required from John Deere.
 EP Mtg. was fitted to tractor with 9.5x24 front tires
 EQ Mtg. was fitted to tractor with 7.50x16 front tires
 ER Mtg. was fitted to tractor with 9.5x16 front tires
 ES Mtg. was fitted to tractor with 10x16.5 front tires
 ET Mtg. was fitted to tractor with 6.5x16 front tires
 EU Mtg. was fitted to tractor with 8.3x16 front tires
 EV Mtg. was fitted to tractor with 9.5x22 front tires
 EW Mtg. was fitted to tractor with 29x12.5x15 front tires
 EX Mtg. was fitted to tractor with 23x8.5x12 front tires
 EY Front tire size must be 11.2x24 and wheels must be reversed
 EZ Mtg. fitted to tractor with 13.6x24 front tires that need to be spaced at 67.5" C/C to avoid interference

FA - FZ

FA Mtg. was fitted to tractor with 12.4Rx24 front tires
 FB Mtg. was fitted to tractor with 9.5x18 front tires
 FC Mtg. Was fitted to tractor with 7 x 16 front ag tires.
 FD Mtg. was fitted to tractor with 7x14 front tires
 FE Mtg. was fitted to tractor with 5.0x12 fnt. tires
 FF Mtg. was fitted to tractor with 10.5/80x18 front tires
 FG Mtg. was fitted to tractor with 6x14 front tires
 FH For tractors with W/4-14.9 R28 tires
 FI Mtg. was fitted to tractor with 16.9 x 28 front tires.
 FJ Hose kit C requires hyd block, part# 9613790 from Ford.
 FK For tractors with 16.9x34 rear tires & 12.4x24 front tires
 FL Hose kit C for OC hyd system (not for optional CC or LS).
 FM Hose kit "C" requires plate from Kubota #70002-05272.
 FN Require pump to operate ldr. See dealer on hydraulic hookup
 FO If hyd. adapter blk required, use # 23467 at additional cost

FP 1986 & newer requires LS valve for hose kit "C" X2659. Prior to 1986, order open center valve kit.
 FQ Use hose kit A when tractor equipped with factory joystick
 FR Part# 813097 restrictor valve for all 3/4" MORB hose ends Required at extra cost for hose kit 'A'.
 FS To complete installation #24343 adapter block is required at additional cost when ordering hose kit C. See price list page 33.
 FT If tractor remote valves are at the rear, order 23383 adapter Block at additional cost
 FU Hose kit "C" requires adaptor block, order separately from dealer
 FV For models with SN D422218 or lower with mechanical valve, PB Block is required for hose kit 'C'. Order FNH86013046 for Tractors without 3PTH. Order FNH86013045 for tractors With 3PTH or megaflo.
 FW Can have O/C or L/S hydraulics
 FX For S-SL tractors (gear Pump) order X9793 hose kit "C" class 6. For SLE tractors (variable piston pump) order X9563 hose kit "C" class 6.
 FY Hose kit "C" includes a selector valve at an additional cost
 FZ Earlier models were open center, then changed to load sense. 986 – SNU024000, 1086 – SNU048000, 1486 – SNU026000, 1586 – SNU021000. X2879 for O/C systems.

GA - GZ

GA Must install auxiliary hydraulic pump for loader operation. See dealer for hydraulic hookup.
 GB If equipped with P.S. order X8398 hose kit in place of X7758
 GC W/draft control opt. req hyd. block from Ford PN-SML28859
 GD Tractors without remotes use X7843 hose kit and PB valve
 GE If equipped with P.S.. order X8398 hose kit in place of X7843
 GF Tractors made in Germany with the "Mannheim System" C/C, can use X7026 hose kit "C". Order X2010 valve pkg with ROPS tractors.
 GG Tractors with sn. #'s less than 45200 have O/C hydraulics and sn#'s greater than 45200 have C/C hydraulics
 GH If not equipped with P S use adapt. blk. 102928 at extra cost
 GI Use P/B valve for hose kit "C" and O/C valve for hose kit "B"
 GJ X8443 hose kit requires a selector isolator valve to complete installation, order Part # 811364 at additional cost
 GK If tractor is equipped with remote outlets order X7030 hose kit in place of X7919 and P/B valve
 GL If hyd adapter block is required order part 23467 at added cost
 GM For valve hookup w/o cable system, order X1185 valve stand
 GN Fitted for steering assist cylinder.
 GO Will not fit tractor with swept back front axle.
 GP Kit modification required if front holes are 4" apart side to side.
 GQ Front wheels to be spaced 64.5" C/C to accommodate mtg
 GR P S cylinder may interfere, modification may be needed
 GS For tractor with power steering
 GT Will fit tractors with or without power steering
 GU For tractors with hydrostatic steering only
 GV For tractors with or without hydrostatic steering
 GW For tractors with swept back front axle
 GX For tractor with Carraro front axle
 GY Will not fit with power assist steering
 GZ Mtg. is not for super steer models

HA - HZ

HA For Canadian model tractors with power steering
 HB For orchard model with adjustable swept back front axle
 HC Does not fit with Hydrostatic steering (1 cylinder per side)
 HD Fits tractors with John Deere power steering only
 HE Fits tractors with power steering, and only fits tractors with a 4 bolt hole pattern at belly of tractor
 HF Q9195 mtg. is for tractors with standard steering only
 HG Fits with John Deere power and standard steering
 HH Will not fit 2wd. models - hooks interfere with tie rod
 HI Fits tractors with a BY - speed front axle

- HJ Front tires spaced to 81" C/C to accommodate mounting
- HK Mtg. is for tractors with power steering and Prairie Cab
- HL Will not fit with industrial front axle
- HM For row crop tractor with a round tube front axle
- HN For standard tractor with cast front axle
- HO Will fit tractors with hyd front wheel drive
- HP Steering restriction & fender removal required on 4WD
- HQ Q1434 accommodates 30" row spacing
- HR Use Q9939 mtg. kit for tractor with external steering cyl.
- HS Tractor requires optional dual pump from KUBOTA for mtg to fit.
- HT Use Q9041 mtg. kit for tractor with gearbox steering, and steering cylinder located on left of engine.
- HU Exhaust adapter supplied for relocation of muffler
- HV Muffler interferes on HSL loader, order part # 110927 exhaust adapter, at additional cost
- HW X7232 muffler kit is required with mtg.
- HX X7233 muffler kit is required with mtg.
- HY X7845 muffler kit is required with mtg.
- HZ X8686 muffler kit is required with mtg.

IA - IZ

- IA X1251 muffler kit is required with mtg.
- IB X8515 muffler kit is required with mtg.
- IC X8528 muffler kit is required with mtg.
- ID Will not fit with underslung exhaust
- IE Modification required if horizontal exhaust
- IF Will accommodate power assist cylinder on left side
- IG Fits tractor with an underslung muffler
- IH Exhaust must be vertical through hood
- II If horizontal exhaust, it must be modified to vertical
- IJ Mtg. fits turbo models
- IK Loader interferes with exhaust, requires field modification
- IL Muffler extensions are required to complete mtg., order part #105699 & 105700 at additional cost
- IM Order # 105698 for 1.75 dia exhaust adapter, or 112346 for tractors with a vertical muffler, at additional cost
- IN Does not fit turbo models
- IO X9738 turbo relocation is required at additional cost
- IP Fits with auxiliary fuel tank
- IQ Tractors with auxiliary fuel tank on left side, order # X7509 fuel tank kit at additional cost
- IR Requires X8543 fuel tank kit at additional cost
- IS If tractor is equipped with auxiliary fuel tank order # X9011 fuel tank kit, at additional cost
- IT Will not fit with auxiliary fuel tank on left hand side
- IU Will not fit tractors with plastic fuel tank
- IV Will fit tractors with plastic fuel tank
- IW Wheels min. spacing rear 72" c/c and front 84" c/c
- IX Front tire size 7.50X20
- IY Mtg. was fitted to tractor with 16.9X26 fnt. tires
- IZ Fuel tank must be relocated to clear rear mount

JA - JZ

- JA Contact factory for mtg. hole pattern
- JB Tractor equipped with factory joystick requires male tip 4-813197 at additional cost, or can be bought at John Deere.
- JC Developed for Open Centre tractor hydraulics
- JD Developed for Load Sense tractor hydraulics
- JE
- JF Auxiliary Hydraulic kit AR71331 required from John Deere
- JG Hose kit 'C' for tractors w/3PTH otherwise use X1492
- JH Developed for Supersteer front axle
- JI Mtg. is for tractors with flat hood side panels
- JJ Mtg. is for tractors with protruding hood side panels
- JK Will not fit tractors with ROPS
- JL Tractor equipped with factory cables and joystick standard.
- JM Max. front tire size 16.9 X 30
- JN Tractors without 3 PTH require 24333 block at additional cost to complete hose kit "C".
- JO Contact factory for price on hose kit C

- JP Ballast weight box for 3 pt hitch is recommended
- JQ Mtg was fitted to tractor with turf tires
- JR Max. front tire size 16.4 X 28
- JS Loader must be removed to service air cleaner
- JT Front mount bolts to side of tractor
- JU Front mount bolts to front of tractor
- JV Hose kit 'C' has special joystick mount and valve plate included. (For Allied joystick only). Valve plate fitting may interfere with lift arm on tractors with more than two remote outlets.
- JW For increased rollback, use 695 loader
- JX Subframe ext (X1148) supplied with mounting kit.
- JY For side driveline use Q7015
- JZ Aux. hyd. kit AR71331 or AR85226(4040) may be required with hose kit X1869. (Purchase separately from John Deere)
Note: If hydraulic levers are beside the dash use hose kit X2154.

KA-KZ

- KA Male tip (FNH part # 9846344 required for hose kit 'A'. Hose kit 'A' for use with factory joystick.
- KB Removal/Modification of fnt. deck shield required.
- KC
- KD X1947muffler kit required with mtg kit
Mtg not recommended by Zetor (Motokov).
Damage & Liability waiver required from Allied factory.
- KE
- KF Max. working pressure should not exceed 2000 PSI or max. 2.5 DIA lift cyl.
- KG Step removal for modification may be required.
- KH Hose kit 'C' developed for non 3 pth tractor, contact Factory otherwise.
- KI Q3277/Q8804 designed for SN 'UV32336' and lower.
- KJ Front fenders must be removed.
- KK Developed for Terra glide front axle.
- KL Minimum front tire spacing is 60".
- KM Maximum hydraulic working pressure 2000 PSI.
- KN Use Q1089 for tractor with MF rear axle. Use Q2619 for tractor with White rear axle.
- KO For narrow front mount S/N UV32337 & greater
- KP Max. front tire spacing is 60"
- KQ Muffler modification required if located on left Side of engine
- KR For hydrostatic steering only, use Q7830 for Manual/cyl assist steering
- KS Mounted with optional Firestone industrial tires
- KT Fitted to tractor with 18 x 8.50-8 front turf tires
- KU Loader is offset 1" right & 2.25" further back than Q2104
- KV Jodale Perry Cab pedal cover requires modification.
- KW For optional LS hydraulic use X2263 hose kit "C".
- KX For optional PB hydraulics use X1977 hose kit "C".
- KY Tractors equipped with factory joystick and cables must order 24748 LS valve and X2032 bag to complete control package.
- KZ Will accommodate MF1231 mower Series 5757.

LA - LF

- LA X2284 hose Kit "C" class 4 for OC hydraulics or X2286 Hose kit "C" class 6 for LS hydraulics.
- LB Valve section end cover AL118486 is required from John Deere when ordering hose kit 'C'.
- LC Valve section end cover AL77030 is required from John Deere when ordering hose kit 'C'.
- LD X2304 Hose Kit "A" required for remotes located on LH deck. John Deer hydraulic tips required.
- LE X2303 Hose Kit "A" Requires remotes located on the LH deck. John Deer hydraulic tips required.
- LF Mounting Kit is not suited for Bi-directional tractor.
- LG Will accommodate RCK60-24B belly mower. (AB not required)
- LH Developed for tractors with Cummins B5.9 engine and Synchro Shuttle transmission.
- LI Max. front tire size 200-70R16
- LJ Power beyond kit required from Case for hose kit "C".

LK For tractors without 3PTH otherwise use X2496 hose kit C
 LL Contact factory to verify sideplate bolt pattern. Engine bolt positions vary by model; verify sideplate clearance holes.
 LM 2595 Short loader will suit 14.9 R24 front tire size
 LN Mounting for non turbo engine only
 LO Mounting for turbo engine only
 LP Mounting suits "new" & "old" Gemini castings
 LQ Mounting suits John Deere hydraulic assist front axle only
 LR Engine side-rail required, tractors prior to SN 166315B
 LS Front tire size: 360/70R-20
 LT Front tire size: 380/85R-28
 LU Front tire size: 420-85R-28
 LV Front tire size: 420/70R-24
 LW Front tire size: 380/70R-24
 LX Front tire size: 480/65R-24
 LY Front tire size: 10.0-16
 LZ Front tire size: 11.0-16

MA – MZ

MA Front tire size: 480/70R-24
 MB Front tire size: 16.9 R24
 MC Front tire size: 12.4 R28
 MD Min. tire spacing is 72". For 60" row spacing use axle bar kit "X2520" at additional cost.
 ME For tractors with JD mounted Valve & joystick use hose kit X2567 class 7.
 MF Will restrict oscillation and/or steering.
 MG For tractors with Cummings engine use Q1702 mtg kit.
 MH For tractors with Agco Allis 666T engine.
 MI For pre 2001 use Q1258, for 2001+ newer use Q2532 on tractors with large axle.
 MJ Upright pin must be reversed for greasing.
 MK With factory joystick (254288A2-Case, 254288A3-McCormick), order X3228 (3 spool) or X3262 (2 spool) which come complete with valve, hoses and all required hardware. Contact factory for price.
 ML Minimum front wheel spacing is 74".
 MM Use hose kit X2674 (class 7) for FNH midmount valve and factory joystick.
 MN Use Q1904 for pre-2002 smaller axles.
 MO If tractor is equipped with remote outlets order X2303 (hose kit A) hose kit in place of X1919 and PB valve.
 MP Use Q8499 mtg kit for German models with French engine.
 MQ When using hose kit 'B', the return tractor remote check valve must be disabled.
 MR Mtg was fitted to tractor with 280-70 R16 front tires.
 MS Mtg was designed for 480/70R 30 front tires.
 MT Auxiliary valve hookup not recommended by John Deere.
 MU Will allow 60" row centers.
 MV Fenders must be removed for 60" row centers only.
 MW Does not fit 231S model.
 MX Doesn't exist.
 MY Carraro independent front suspension option requires field modification of tractor valve support bracket.
 MZ S2795 loader will suit 14.9 R28 tires.

NA – NZ

NA Mounted with fenders.
 NB If hydraulic valve is under the dash, use hose kit X2154 (class 3). If hydraulic valve is at the rear, use hose kit X1869 (class 4). Block AR71331 is required from John Deere.
 NC Side marker light modification required.
 ND If joystick is desired instead of levers, use hose kit X2864 (class 4). with X2024 valve kit.
 NE Hose kit C requires dealer installed power beyond ready kit.
 NF Use X2899 (class 9) hose kit for factory electronic joystick mounted in arm rest.

NG Requires 2 cable connectors 814158 at extra cost.
 NH Mtg kit won't fit selecto-matic series (insufficient rear mounting points).
 NI PB block 24525 required for hose kit 'C' at additional cost.
 NJ Axle bars will not fit 60" row centers and/or auxiliary fuel tank.
 NK Order hose kit X2992 (class 9) for factory installed valve and joystick.
 NL Mtg kit only bolts to optional factory rear loader 90-deg side plate brackets (required)
 NM Use X2989 hose kit 'A' with factory joystick.
 NN Use Q2969 for newer models with front mounted battery box.
 NO Order subframe extension kit X1148.
 NP With factory joystick, use hose kit 'C' X2977 (class 20) (includes 2 spool valve).
 NQ Doesn't exist.
 NR For older non-Bosch hydraulics without power beyond Cap, order X2950 and PB block 24525.
 NS Valve, joystick, cables and all required fittings included in the hose kit.
 NT 60" row centers may not allow grill guards.
 NU Early production models may use 5/8" bolts for rear two Bolts. Installer must drill and tap for 3/4" bolts. Contact John Deere or Buhler Engineering for further details.
 NV Order X3141 (class 8) hose kit for factory valve and joystick.
 NW Allows factory front 3 point hitch.
 NY With factory joystick, use hose kit 'C' X3190.
 NZ Mounted with factory mower deck MF2325.

OA - OZ

OA Does not fit with Terraglide system.
 OB Order 116743 exhaust offset for 345, 116744 exhaust offset for 445/GL45SS.
 OC Standard/Economy tractors equipped with open center hydraulics.
 OD Order poppet valve kit from CNH to complete hose kit C (part no. SBA340170980).
 OE Order X3271 (class 7) hose kit for factory valve and joystick.
 OF Order X3344 (class 9) hose kit for factory valve and joystick.
 OG If hyd levers are to the left of the steering wheel, X2154 hose kit will not work.
 OH Front wheels must be spread to 49.5" for 9.5-16 tires.
 OI Order kit M3326 when tractor equipped with factory 90-deg mounting sideplates.
 OJ Tractor hydraulics run at low pressure. Additional pump may be required for loader operation.
 OK Hose kit "A" for use with factory joystick. MF male tips required.
 OL Hose kit X3143 (class 1) works with new tractors that have PB block with 3 ports. Use X1989 (class 3) with older tractors that have PB block with only 2 ports.
 OM Order hose kit X3403 (class 1) when tractor equipped with factory joystick and valve.
 ON X3341 muffler kit is required with mounting.
 OO Tractor body must be 20.63" to fit mount.
 OP Use Q3378 if tractor has steering rod along LH side.
 OQ Order hose kit X3429 (hose kit A) when tractor equipped with factory joystick and valve.
 OR Earlier models may have smaller hydraulic tubing with 7/8" MJIC thread on split. X2858 required.
 OS Developed for IVT model. Does not fit Powershift.
 OT Does not fit models with Dyna 4 transmission.
 OU Does not fit with Tier II engines (oil filter on the right, 4-bolt muffler flange).
 OV Exhaust adapter fits older units with 2-bolt muffler flange.
 OW Kit developed for older 3 cyl models (interferes with starter and exhaust on newer 4 cyl models).
 OX Delta series has Open Center hydraulics; Plus and Elite are Closed Center Load Sensing (use X2041N and X2993 hose kit).
 OY Hose kit works with 2 remotes only. Third remote creates interference with lift arms.
 OZ New Veco engine causes interference on RHS side of mount.

PA – PZ

- PA For tractor with Independent front suspension
- PB Hydraulic fittings are included in Hose kit "C".
- PC Mtg was fitted to tractor with 9.5x24 rear tires.
- PD Hose kit "C" requires hyd block, SML53849 from New Holland.
- PE Will not fit Quad Shift or Dynashift.
- PF If tractor equipped with a factory valve and joystick under the cab order Deluxe hose kit A - X3647 Class 19 (valve to loader) that includes a 3 spool Hydrafast.
- PG Puma 165 with fenders requires X3652 Fender Kit at additional cost.
- PH Factory installed Tool Box must be removed.

- PI Battery box, fuel tank, and steps must be removed for Mt. Kit installation.
- PJ Order X3681(class 6) Deluxe Hose Kit A for tractors equipped with electronic joystick.
- PK Order X3683 (class 1) Deluxe Hose Kit A with male tips for tractors equipped with valve under the cab.
- PL Mount not designed to fit tractors with suspension.
- PM Order Deluxe Hose Kit A for tractor equipped with auxiliary factory valve X3735.
- PN Order Deluxe Hose Kit A for tractor equipped with auxiliary factory valve X3751(class 5).
- PM Fitted with 380/85 R34 front and 480/80 R46 rear tires.
- PN Hose kit C includes 6 spool valve and hydra fast. Dealer must order the factory joystick (254288A2-Case, 254288A3-McCormick) in order to operate the auxiliary valve.
- PO Was fitted with belly mount mower MWX60S.
- PQ Axle brackets not used with belly mount mower and axle bracket on center mount must be trimmed to accommodate mower linkage. (Note: WILL NOT WORK WITH MOWER DECK LARGER THAN 54")
- PR Minimum front wheel spacing is 47.5" center to center.
- PS Will not fit Evolution Series.
- PT Mounted with wheel spacing of 80.5".
- PU Steering Radius must be reduced to allow for fender clearance if applicable.