

# Specifications

SERIES	30		45			60		80			100		150			
MODEL	C8315	C8317	C60SS	C72SS	C84SS	C8801	C8800	C7080	C8080	C9080	C8100	C9100	C8150	C9150	C10150	
Maximum hp	30	30	45	45	45	60	60	80	80	80	100	100	150	150	150	
3-point hitch	Category I		Category I			Category I & II		Category II			Category II & III		Category II & III			
Moldboard thickness	¼"		¼"			¼"		¼" Boxed reinforcement			5/16" Boxed reinforcement					
Moldboard width	60"	72"	60"	72"	84"	84"	96"	84"	96"	108"	96"	108"	96"	108"	120"	
Moldboard height	12 ½"		13"			16"		18"			18"		18"			
Adjustment	Manual 5-position		Manual 5-position			Manual 5-position		Manual or hydraulic			Manual or hydraulic		Manual or hydraulic			
Adjustment, angle	30° left or right		40° left or right			40° left or right		30° left or right			30° left or right		30° left or right			
Adjustment, hydraulic cylinder adjustment	N/A		N/A			Optional		N/A			N/A		N/A			
Adjustment, tilt	3-point hitch linkage adj.		Manual 15° blade adjustment			3-point hitch linkage adj.		Manual or hydraulic 13° blade adjustment								
Offset	N/A		N/A			N/A		Manual or hydraulic 20° left or right								
Sideshift	N/A		Up to 12" off center			N/A		N/A			N/A		N/A			
King pin	N/A		N/A			N/A		3"			3 1/2"		4"			
Cutting edge	¼" x 3" reversible		High carbon ½" x 6" reversible					High carbon ½" x 6" reversible								
Weight, lb	155	180	263	283	289	405	450	939	969	989	1287	1352	1645	1668	1703	
Dual gauge wheel kit	N/A		N/A			N/A		Optional			Optional		Optional			
Skid shoes	N/A		N/A			N/A		Optional			Optional		Optional			
Racket jack	N/A		N/A			N/A		Optional			Optional		Optional			

