

Specifications

MODEL	YC5010	YC6010	YC7420	YC8420	YC9620Q	YC1080C	YC1080D
Cutting width	50"	60"	74"	85"	96"	108"	108"
Cutting height	25"	25"	30"	33"	36"	41"	41"
Replaceable cutting edge	N/A	N/A	N/A	N/A	N/A	Yes	Yes
Fan - 3-blade Fan - 4-blade	Standard Optional	Standard Optional	Standard Optional	Standard Optional	Standard Optional	N/A Standard	N/A Standard
Fan diameter	20"	22"	24"	25"	34"	36"	36"
Replaceable fan housing	N/A	N/A	N/A	N/A	N/A	7 gauge	7 gauge
Drive fan	540 rpm open gear	540 rpm open gear	540 rpm open gear	540 rpm oil bath gearbox	540 rpm oil bath gearbox	540 rpm oil bath gearbox	540 rpm direct drive
Auger diameter	13"	15"	15"	20"	15" (dual)	15" (dual)	15" (dual)
Auger drive	#50 chain	#50 chain	#50 chain	#60 chain	#60 chain	#80 chain	#80 chain
Spout rotator - manual (hand crank) - hydraulic	Standard Optional	Standard Optional	Optional Standard	Optional Standard	Optional Standard	N/A Standard	N/A Standard
Spout deflector - manual (6 position) - hydraulic	Standard Optional	Standard Optional	Standard Optional	Standard Optional	Standard Optional	N/A Standard	N/A Standard
Skid shoes	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable
Hitch category	Cat. I standard	Cat. I standard	Cat. I standard Cat. II bushings Cat. I & II heavy frame optional	Cat. II std Cat. II Q.H. std Cat. III Q.H. narrow	Cat. I & II std Cat. II Q.H. std Cat. III Q.H. narrow	Cat. II std Cat. III Q.H. std Cat. III Q.H. narrow	Cat. II std Cat. III Q.H. std Cat. III Q.H. narrow
Hitch adjustment	4 position	4 position	2 position	2 position	Fixed	2 position	2 position
HP requirement	15 - 30	20 - 40	40 - 70	60 - 90	90 - 125	120 - 180	120 - 180
Weight	422 lbs	470 lbs	756 lbs	966 lbs	1243 lbs	2398 lbs	2314 lbs

