

Specifications

MODEL	Y450	Y550	Y650	Y750
Cutting width	48"	60"	72"	84"
Cutting height	1 ½" to 4 ½"	1 ½" to 4 ½"	1 ½" to 4 ½"	1 ½" to 4 ½"
Blade tip speed	15,485 ft/min	15,829 ft/min	18,737 ft/min	18,552 ft/min
Blades	3	3	3	3
Blade material	¼" x 2 ½" alloy hardened	¼" x 2 ½" alloy hardened	¼" x 2 ½" alloy hardened	¼" x 3" alloy hardened
Blade length	17 ¾"	21 ¾"	25 ¾"	29 ¾"
Blade overlap	1 5/8"	2 5/8"	2 5/8"	2 5/8"
Blade drive	2 belt B groove	2 belt B groove	2 belt B groove	2 belt B groove
Deck material	10 gauge	7 gauge	7 gauge	7 gauge
Gearbox	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)
Gearbox ratio	1 : 1.93	1 : 1.93	1 : 1.93	1 : 1.93
Tractor hp requirement	12 - 25	15 - 30	20 - 40	25 - 45
3-point hitch*	Cat. I	Cat. I	Cat. I	Cat. I
Tires	4.10 / 3.50 - 4	4.10 / 3.50 - 4	4.10 / 3.50 - 4	13 x 5.0 x 6
Spindles	Cast w/bearing	Cast w/bearing	Cast w/bearing	Cast w/bearing
Front roller	3" x 4"	3" x 4"	4" x 5 3/8"	4" x 5 3/8"
UHMW poly roller (optional)	4" x 7"	4" x 7"	4" x 7"	4" x 7"
Weight	440 lb	552 lb	618 lb	724 lb

