

## Specifications

MODEL	1520
Cutting width	180" (4.57 m)
Overall width	190" (4.83 m)
Overall length	202" (5.13 m)
Transport width	99" (2.51 m)
Transport height	84" (2.13 m)
Deck thickness	7 gauge (3/16", 4.6 mm)
Cutting height	1.75" - 16.75" (44.5 mm - 425 mm)
Ground clearance	14.75" (42.5 mm)
Cutting capacity	4" (101.6 mm)
Blade overlap	6.5" (165.1 mm)
Divider gearbox rating	260 hp (194 kw)
Center & wing gearbox rating	210 hp (142 kw)
Output shaft	2.38" (60.3 mm)
Side skirt depth & thickness	13.63" (346 mm) & 1/4" (6.35 mm)

MODEL	1520
Blade tip speed - center - wing	540 RPM 15,980 ft/min (4871 m/min) 15,459 ft/min (4711 m/min)
Blade tip speed - center - wing	1000 RPM 15,974 ft/min (4869 m/min) 15,708 ft/min (4788 m/min)
Wing working range	25° down to 87° up
Wing floating range	25° down to 87° up
Drive size, main	Cat. 5 CV (1000 RPM), Cat. 6 CV (540 RPM)
Drive size, center/wings	Category 5
Suspension	Rubber grommett 3 puck system
Tires	Laminated
Tractor PTO speed	540 or 1000 RPM
Tractor hp	85 hp (63 kW)
Weight	4,500 lb (2041 kg) to 5,050 lb (2291 kg)

