

Specifications

SERIES	I	
MODEL	Y410LS	Y510LS
Cutting width	48"	60"
Cutting height	Min: 3"	Min: 4"
Blade tip speed	13,098 ft/min	12,721 ft/min
Spring steel blades	½" x 3" heat treated	½" x 3" heat treated
Deck material	11 gauge	11 gauge
Gearbox	Closed (540 RPM)	Closed (540 RPM)
Gearbox rating	30 hp	40 hp
Tractor HP requirement	20 - 45	25 - 55
PTO shaft	Shear pin	Shear pin
3-point hitch*	Cat. I standard	Cat. I standard
Tire - 3-point	15" laminated	15" laminated
Tire / wheels - trailing	n/a	n/a
Stump-jumper	n/a	n/a
Parking jack	n/a	n/a
Chain kit	Optional	Optional
Weight - 3-point	450 lb	520 lb
Weight - trailing	n/a	n/a

II		
Y510	Y620	Y720
60"	72"	84"
Min: 4"	Min: 4"	Min: 4"
12,721 ft/min	14,758 ft/min	14,283 ft/min
½" x 3" heat treated	½" x 3" heat treated	½" x 3" heat treated
10 gauge	10 gauge	10 gauge
Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)
40 hp	60 hp	65 hp
25 - 65	35 - 65	45 - 75
Shear pin	Slip clutch	Slip clutch
Cat. I standard	Cat. II standard	Cat. II standard
16" solid rubber	16" solid rubber	20" solid rubber
Solid rubber or 15" rim	Solid rubber or 15" rim	15" rim
Standard: 24" diameter	Standard: 24" diameter	Standard: 24" diameter
Optional	Optional	Optional
Optional	Optional	Optional
601 lb	777 lb	989 lb
686 lb	856 lb	1080 lb

