

## Specifications

SERIES	25			45		65				
	MODEL	C2540	C2548	C2560	C4560	C4572	C6550	C6560	C6572	C6582
Tillage width	36"	45"	54"	55"	69"	46"	56"	68"	77"	
Overall width	46 1/2"	54 1/2"	66 1/2"	66"	78"	56"	66"	78"	88"	
Tractor HP requirement	12 - 18	14 - 22	18 - 25	25 - 40	30 - 45	30 - 40	35 - 45	45 - 55	55 - 65	
3-point hitch	Cat. I			Cat. I		Cat. I, optional fit Cat. II				
Gearbox	Heavy-duty oil bath (540 RPM)			Heavy-duty oil bath (540 RPM)		Heavy-duty oil bath (540 RPM)				
Chain in oil bath	#60H	#60H	#60H	#80H	#80H	#100H	#100H	#100H	#100H	
Rotor speed RPM	196 RPM or 880 ft/min			203 RPM or 865 ft/min		196 RPM or 880 ft/min				
Sideshift	2 1/2"	4 1/2"	7 1/2"	6 3/4"	8 1/2"	5"	8"	15"	n/a	
PTO shaft	Slip clutch, shear bolt optional			Slip clutch		Slip clutch				
Tine size	1/4" x 2 1/4"	1/4" x 2 1/4"	1/4" x 2 1/4"	1/4" x 2 1/4"	1/4" x 2 1/4"	5/16" x 3 1/4"	5/16" x 3 1/4"	5/16" x 3 1/4"	5/16" x 3 1/4"	
Number of tines	4 flanges 4 tines/flange	5 flanges 4 tines/flange	6 flanges 4 tines/flange	6 flanges 4 tines/flange	8 flanges 4 tines/flange	5 flanges 6 tines/flange 4 tine opt.	6 flanges 6 tines/flange 4 tine opt.	7 flanges 6 tines/flange 4 tine opt.	8 flanges 6 tines/flange 4 tine opt.	
Skid shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Weight	425 lbs	458 lbs	517 lbs	613 lbs	688 lbs	774 lbs	835 lbs	906 lbs	968 lbs	

