

Front-End Loader - 95 Series

Model	95	195	295	395	495	495 S
Maximum lift height to pivot pin (in)	78	90	112	118	127	122
Reach at maximum lift height (in)	N/A	15	22	20	28	33
Maximum dump angle (deg)	45	40	25	27	38	38
Maximum rollback angle (deg)	14	19	32	31	23	20
Digging depth (in)	3.9	3.3	2.2	2.9	5.2	5.2
Overall height in carry position (in)	48	51	59	59	67	67
Lift capacity to maximum height - at pivot point (lb.) optional cylinder	525	1150	1625 2775	1500 2650	2075 3300	2100 3340
Lift capacity to maximum height (lb.) optional cylinder	350	775	1150 1975	1075 1875	1375 2175	1400 2214
Breakout force - at pivot point (lb.) optional cylinder	1200	2175	2775 4675	2425 4150	3475 5375	3750 5775
Breakout force (lb.) optional cylinder	850	1600	2150 3600	1900 3275	2500 3875	2650 4075
Hydraulic pressure rating/flow rate (psi)/(gpm)	1800/5	2000/5	2500/10		2500/10	
Tractor size (HP @ normal duty)	15-25	20-35	30-45	35-75	50-100	
Weight (with bkt & mtg kit) (lb.)	475	775	1285	1515	2070	

Model	595	595 S	695	795	795 S	895	895 S
Maximum lift height to pivot pin (in)	136	131	150	161	154	168	168
Reach at maximum lift height (in)	32	37	30	26	34	29	41
Maximum dump angle (deg)	41	41	59	32	32	40	40
Maximum rollback angle (deg)	18	18	34	21	22	22	22
Digging depth (in)	5.5	5.5	9.1	4.4	4.4	4.5	4.5
Overall height in carry position (in)	75	75	79	81	80	86	86
Lift capacity to maximum height - at pivot point (lb.) optional cylinder	2425 3775	2450 3800	3275	3100	3175	4675	4675
Lift capacity to maximum height (lb.) optional cylinder	1650 2575	1675 2614	2225	2075	2100	3325	3325
Breakout force - at pivot point (lb.) optional cylinder	5425 8200	5825 8800	7375	6825	7500	10150	10150
Breakout force (lb.) optional cylinder	3875 5875	4125 6175	5400	5050	5425	7600	7600
Hydraulic pressure rating/flow rate (psi)/(gpm)	2500/15		2500/15	2500/15		2500/20	
Tractor size (HP @ normal duty)	50-120		75-150	75-150		130-190	
Weight (with bkt & mtg kit) (lb.)	2190		2585	2760		3390	

Front-End Loader - Midmount 2000 Series

Model	2095	2195	2295	2395	2495	2495 TSL	2495 S	2495 S TSL	2595 2596	2595 2596 TSL	2595 S	2595 S TSL
Maximum lift height to pivot pin, in	76	102	112	123	140	140	136	136	145	145	142	142
Reach at maximum lift height, in	21	30	22	15	21	21	25	25	29	28	32	32
Maximum dump angle, deg	46	50	51	49	44	44	44	44	48	49	46	48
Maximum rollback angle, deg	22	36	33	39	41	41	41	41	38	38	38	38
Digging depth, in	4.0	3.7	4.0	4	5.0	5.0	5.0	5.0	7.0	7.0	5.5	5.5
Overall height in carry position, in	41	48	58	58	83	86	83	86	85	87	85	86
Lift capacity to max height - at pivot point, lb. optional cylinder	855	1295	3477	3330	4015 6250	6250	4060 6315	6270	3425 5395	5355	3465 5455	5410
Lift capacity to max height, lb. optional cylinder	598	853	2560	2450	2605 4050	4050	2620 4075	4045	2330 3670	3645	2335 3680	3650
Breakout force - at pivot point, lb. optional cylinder	1420	2360	5656	4871	4845 7535	7545	5215 8070	8005	4795 7490	7425	5180 8040	7970
Breakout force, lb. optional cylinder	1004	1738	4349	3858	3515 5465	5475	3715 5750	5705	3480 5435	5385	3695 5735	5690
Hydraulic pressure rating/flow rate, psi/gpm	1800/5	2000/5	2500/10		2500/15				2500/15			
Tractor size (HP @ normal duty)	15-25	20-35	30-45	35-75	50-100				50-120			
Weight (with bkt & mtg kit), lb.	500	600	1380	1395	2100				2200			

Model	2695	2795 HD	2795 HD TSL	2795 HD S	2795 HD S TSL	2895	2895 TSL	2895 S	2895 S TSL	3995 TSL
Maximum lift height to pivot pin, in	157	164	164	157	157	181	181	169	169	181
Reach at maximum lift height, in	37	29	29	37	37	29	29	20	20	29
Maximum dump angle, deg	50	50	50	50	51	62	61	62	61	61
Maximum rollback angle, deg	34	34	34	34	34	37	37	37	37	37
Digging depth, in	4.0	5.0	5.0	4.0	4.0	5.0	5.0	5.0	5.0	5.0
Overall height in carry position, in	86	86	87	86	87	101	103	101	103	103
Lift capacity to max height - at pivot point, lb. optional cylinder	3770	3685	3680	3770	3760	7000	6900	6900	6875	6900
Lift capacity to max height, lb. optional cylinder	2660	2610	2605	2660	2665	4950	4950	4925	4925	4950
Breakout force - at pivot point, lb. optional cylinder	7145	6440	6460	7145	7160	8475	8500	9950	9950	8500
Breakout force, lb. optional cylinder	5185	4780	4795	5185	5190	6550	6550	7450	7475	6550
Hydraulic pressure rating/flow rate, psi/gpm	2500/15					2500/20				2500/20
Tractor size (HP @ normal duty)	75-130	75-130				130-275				150-300
Weight (with bkt & mtg kit), lb.	2800	2800				3800				4275